





GRADE: <b>N40</b>	PROPRIETARY AND CONFIDENTIAL	UNLESS OTHERWISE SPECIFIED:	NAME		DATE	(n	AMAZI	
MAGNETIZED: YES	THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF AMAZING MAGNETS LLC ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF AMAZING MAGNETS LLC IS PROHIBITED.	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: MACH ± 1° TWO PLACE DECIMAL ± 0.01 THREE PLACE DECIMAL ± 0.005	DRAWN	LB	1/18/2012	U	MAGNE	:TS
RESIDUAL INDUCTION (Br): 12.5-12.8 KG			CHECKED	ТВ	1/18/2012	TITLE:	C625E	
COERCIVE FORCE (Hc): ≥ 11.4 KOe		MATERIAL:	COMMENTS: ALL EDGES BROKEN 0.025 MAX					
INTRINSIC COERCIVE FORCE (Hci): ≥ 12.0 KOe		NdFeB				SIZE DW	DWG. NO.	REV
MAX. ENERGY PRODUCT (BHmax): 38-41 MGOe	CAGE CODE	Ni-Cu-Ni (silver in Color)				A	C625E-SPECS	O
MAX OPERATIONAL TEMP: 80C / 176F	4R1R7	DO NOT SCALE DRAWING				SCALE 1:1		
_	1				_			

5 4 3 2