


GRADE: <b>N40</b>	<b>PROPRIETARY AND CONFIDENTIAL</b>	<b>UNLESS OTHERWISE SPECIFIED:</b>  DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL $\pm 1/64$ ANGULAR: MACH $\pm 1^\circ$ TWO PLACE DECIMAL $\pm 0.01$ THREE PLACE DECIMAL $\pm 0.005$	NAME		DATE
MAGNETIZED: <b>YES</b>			DRAWN	LB	12/13/201
RESIDUAL INDUCTION (Br): <b>12.5-12.8 KG</b>			CHECKED	TB	12/13/201
COERCIVE FORCE (Hc): $\geq 11.4$ KOe			COMMENTS:		
INTRINSIC COERCIVE FORCE (Hci): $\geq 12.0$ KOe			ALL EDGES BROKEN 0.025 MAX		
MAX. ENERGY PRODUCT (BHmax): <b>38-41 MGOe</b>	CAGE CODE <b>4R1R7</b>	FINISH: <b>Ni-Cu-Ni</b> (silver in Color)			
MAX OPERATIONAL TEMP: <b>80C / 176F</b>		DO NOT SCALE DRAWING			

 <b>AMAZING MAGNETS®</b>		
TITLE: <b>D094C</b>		
SIZE <b>A</b>	DWG. NO. D094C-SPECS	REV <b>0</b>
SCALE 4 : 1		

5

4

3

2

1