





## NOTES: BLACK EPOXY COATING OVER NI-Cu PLATING

							AMAZII	NG
GRADE: N40	PROPRIETARY AND CONFIDENTIAL	UNLESS OTHERWISE SPECIFIED:	NAME		DATE	□(( <b>++</b> )		
Magnetized: <b>YES</b>	THE INFORMATION CONTAINED IN THIS	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/64	DRAWN	CW	7-26-2018		MAGNE	:15
RESIDUAL INDUCTION (Br): 12.5-12.8 KG	DRAWING IS THE SOLE PROPERTY OF AMAZING MAGNETS LLC ANY REPRODUCTION IN PART OR AS A WHOLE	ANGULAR: MACH ± 1° TWO PLACE DECIMAL ± 0.01 THREE PLACE DECIMAL ± 0.005	CHECKED	LB	7-26-2018	TITLE:	R250A2-BE	•
COERCIVE FORCE (Hc): ≥11.4 KOe	WITHOUT THE WRITTEN PERMISSION OF AMAZING MAGNETS LLC IS		COMMENTS:		,			
INTRINSIC COERCIVE FORCE (Hci): ≥ 12.0 KOe	PROHIBITED.	NdFeB	ALL EDGES BROKEN 0.025 MAX			SIZE DWG		REV
MAX. ENERGY PRODUCT (BHmax): 38-41 MGOe	CAGE CODE	Ni-Cu-BE (Black in Color				A	R250A2-BE-SPECS	0
MAX OPERATIONAL TEMP: 80C / 176F	4R1R7	DO NOT SCALE DRAWING				SCALE 4:1		
5	4	3			2		1	