





			i				AMAZI	NG
GRADE: N40	PROPRIETARY AND CONFIDENTIAL	UNLESS OTHERWISE SPECIFIED:	NAME		DATE	. II. ++ JI	MAGNE	TOR
magnetized: <b>YES</b>	THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF AMAZING MAGNETS LLC ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF AMAZING MAGNETS LLC IS PROHIBITED.	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: MACH ± 1° TWO PLACE DECIMAL ± 0.01 THREE PLACE DECIMAL ± 0.005	DRAWN	LB	1/24/2012		IVIAGIVE	: 1 3
RESIDUAL INDUCTION (Br): 12.5-12.8 KG			CHECKED	TB	1/24/2012	TITLE:	CUPH1500	
COERCIVE FORCE (Hc): ≥ 11.4 KOe			COMMENTS: ALL EDGES BROKEN 0.025 MAX					
INTRINSIC COERCIVE FORCE (Hci): ≥ 12.0 KOe		NdFeB				SIZE DWG. NO.  CUPH1500-SPEC		REV O
MAX. ENERGY PRODUCT (BHmax): 38-41 MGOe	CAGE CODE	Ni-Cu-Ni (silver in Color)			CUPH1500-SPECS			
MAX OPERATIONAL TEMP: 80C / 176F	4R1R7	DO NOT SCALE DRAWING				SCALE 1:1		
5	4	3	2			1		