



GRADE: N42
MAGNETIZED: YES
RESIDUAL INDUCTION (Br): 12.8-13.2 KG
COERCIVE FORCE (Hc): \geq 11.4 KOe
INTRINSIC COERCIVE FORCE (Hci): \geq 12.0 KOe
MAX. ENERGY PRODUCT (BHmax): 40-43 MGOe
MAX OPERATIONAL TEMP: 80C / 176F

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF AMAZING MAGNETS LLC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF AMAZING MAGNETS LLC IS PROHIBITED.
CAGE CODE 4R1R7

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL \pm 1/64 ANGULAR: MACH \pm 1° TWO PLACE DECIMAL \pm 0.01 THREE PLACE DECIMAL \pm 0.005
MATERIAL: NdFeB
FINISH: Ni-Cu-Ni (silver in Color)
DO NOT SCALE DRAWING

NAME	DATE
DRAWN LB	12/13/2011
CHECKED TB	12/13/2011
COMMENTS: ALL EDGES BROKEN 0.025 MAX	



AMAZING MAGNETS®

TITLE: **DH125F-FS-N42**

SIZE A	DWG. NO. DH125F-FS-N42	REV 0
------------------	---------------------------	-----------------

SCALE 2 : 1

5

4

3

2

1