



GRADE: <b>N40</b>
MAGNETIZED: <b>YES</b>
RESIDUAL INDUCTION (Br): <b>12.5-12.8 KG</b>
COERCIVE FORCE (Hc): <b>≥ 10.9 KOe</b>
INTRINSIC COERCIVE FORCE (Hci): <b>≥ 12.0 KOe</b>
MAX. ENERGY PRODUCT (BHmax): <b>38-41 MGOe</b>
MAX OPERATIONAL TEMP: <b>80C / 176F</b>

<b>PROPRIETARY AND CONFIDENTIAL</b>
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF AMAZING MAGNETS LLC ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF AMAZING MAGNETS LLC IS PROHIBITED.
CAGE CODE <b>4R1R7</b>

<b>UNLESS OTHERWISE SPECIFIED:</b>
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: MACH ± 1° TWO PLACE DECIMAL ± 0.01 THREE PLACE DECIMAL ± 0.005
MATERIAL: <b>NdFeB</b>
PLATING/COATING: <b>Ni-Cu-Ni</b>
DO NOT SCALE DRAWING

NAME	DATE
DRAWN L.Bilisoly	5/3/2019
CHECKED	5/3/2019
COMMENTS: ALL EDGES BROKEN 0.25" MAX	

# AMAZING MAGNETS®

TITLE: <b>DH125H-FS</b>	
SIZE <b>A</b>	DWG. NO. DH125H-FS-SPECS
REV <b>0</b>	

5

4

3

2

1