


GRADE: C8
MAGNETIZED: YES
RESIDUAL INDUCTION (Br): 3.85 KG
COERCIVE FORCE (Hc): \geq 2.95 KOe
INTRINSIC COERCIVE FORCE (Hci): \geq 3.05 KOe
MAX. ENERGY PRODUCT (BHmax): 3.5 MGOe
MAX OPERATIONAL TEMP: 460C / 860F

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF AMAZING MAGNETS LLC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF AMAZING MAGNETS LLC IS PROHIBITED.
CAGE CODE 4R1R7

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL \pm 1/64 ANGULAR: MACH \pm 1° TWO PLACE DECIMAL \pm 0.01 THREE PLACE DECIMAL \pm 0.005
MATERIAL: Ferrite (Ceramic)
FINISH: NO FINISH (BLACK IN COLOR)
DO NOT SCALE DRAWING

NAME	DATE
DRAWN LB	1/18/2012
CHECKED TB	1/18/2012
COMMENTS: ALL EDGES BROKEN 0.025 MAX	

 AMAZING MAGNETS®		
TITLE: P295-147-625-F		
SIZE A	DWG. NO. P295-147-625-F-SPECS	REV 0
SCALE 1 : 1		