



AMAZING  
MAGNETS®



GRADE: <b>N40</b>	<b>PROPRIETARY AND CONFIDENTIAL</b>	<b>UNLESS OTHERWISE SPECIFIED:</b>	NAME	DATE	 <b>AMAZING MAGNETS®</b>
MAGNETIZED: <b>YES</b>	THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF AMAZING MAGNETS LLC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF AMAZING MAGNETS LLC IS PROHIBITED.	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL $\pm 1/64$ ANGULAR: MACH $\pm 1^\circ$ TWO PLACE DECIMAL $\pm 0.01$ THREE PLACE DECIMAL $\pm 0.005$	DRAWN	LB	
RESIDUAL INDUCTION (Br): <b>12.5-12.8 KG</b>			MATERIAL:	CHECKED	TB
COERCIVE FORCE (Hc): $\geq 11.4$ KOe		CAGE CODE	FINISH:	COMMENTS: ALL EDGES BROKEN 0.025 MAX	
INTRINSIC COERCIVE FORCE (Hci): $\geq 12.0$ KOe	<b>4R1R7</b>	<b>NdFeB</b>			
MAX. ENERGY PRODUCT (BHmax): <b>38-41 MGOe</b>		<b>Ni-Cu-Ni</b> (silver in Color)	TITLE:		<b>P500-100P</b>
MAX OPERATIONAL TEMP: <b>80C / 176F</b>		<b>DO NOT SCALE DRAWING</b>	SIZE	DWG. NO.	REV
			<b>A</b>	P500-100P-SPECS	<b>0</b>
			SCALE 1 : 1		

5

4

3

2

1